

BMW Motorrad

Maintenance schedule



0406 - R 850 R

00 00 122 BMW Service (see Maintenance Schedule) (initially at 10,000 km, then every 20,000 km)

Customer

Registration No.

Odometer reading

Equipment trim-level variant:

0771 - Cross-spoked wheels

0583 - No catalytic converter

Order No.

Date

Mechanic's + Manager's signature

- | | |
|---|--------------------------|
| Changing engine oil with engine at operating temperature, replacing oil filter | <input type="checkbox"/> |
| Adjusting valve clearance | <input type="checkbox"/> |
| Checking condition of spark plugs | <input type="checkbox"/> |
| Checking freedom of movement of throttle cable and checking for kinks and chafing | <input type="checkbox"/> |
| Checking clutch play | <input type="checkbox"/> |
| Checking front brake pads for wear | <input type="checkbox"/> |
| Checking front brake discs for wear | <input type="checkbox"/> |
| Checking brake-fluid level, front brakes | <input type="checkbox"/> |
| Checking rear brake pads for wear | <input type="checkbox"/> |
| Checking rear brake disc for wear | <input type="checkbox"/> |
| Checking brake-fluid level, rear brake | <input type="checkbox"/> |
| Checking swinging-arm pivot mount | <input type="checkbox"/> |
| Checking steering damper | <input type="checkbox"/> |
| Lubricating side stand | <input type="checkbox"/> |
| Lubricating nipple of clutch cable | <input type="checkbox"/> |
| Checking operation of side-stand switch | <input type="checkbox"/> |
| Checking idle speed | <input type="checkbox"/> |
| Checking/adjusting synchronisation | <input type="checkbox"/> |
| Checking throttle valves | <input type="checkbox"/> |
| Checking CO value | <input type="checkbox"/> |
| Checking spoke tension | <input type="checkbox"/> |
| Checking tyre pressures and tread depth | <input type="checkbox"/> |
| Checking lights and signalling equipment | <input type="checkbox"/> |

Test ride as final inspection and function check

Confirming BMW Service in on-board documentation

BMW Motorrad, UX-VA-4
27.04.06

BMW recommends 